

ULUSAL VAKUM

Industrial Vacuum Cleaners

- ✓ Reduces CNC machine sumps cleaning time
- ✓ Ensures CNC machine sumps remain clean
- ✓ Improves machine performance and reduces downtime
- ✓ Extends coolant life
- ✓ Reduces bacterial growth


ENKAR

İNŞ. TAAH. ve TİC. LTD. ŞTİ.

Ostim OSB Mh. 1201. Cadde
No: 7 Yenimahalle - Ankara / TURKEY
Phone: +90 312 354 0501
Fax: +90 312 354 6719
www.enkar.com.tr • info@enkar.com.tr



Basket and Bag Filter



Discharge Pump

Description

Industrial vacuum cleaner which is designed to suck coolant, swarf and oil from machine tool sumps, filter the swarf and pump filtered coolant back to machine sump for re-use.

Specs

- ✓ Strong suction thanks to 3x 1kW vacuum motors
- ✓ 330lt tank capacity (3mm sheet metal body)
- ✓ Simultaneous suction and discharge
- ✓ 63-200-400µ re-usable bag filter
- ✓ When tank is full, vacuum motors are switched off automatically
- ✓ 330lt suction time with 3 motors < 1min, discharge time < 2.5min
- ✓ Various suction tools
- ✓ High manoeuvrability with swivel casters

Voltage (VAC)	Max Power (w)	Tank Capacity (lt)	Suction Rate (lt / min)	Discharge Rate (lt / min)	Length (mm)	Height (mm)	Width (mm)	Weight (kg)
220	3000	330	330	125	1450	1350	800	191



Basket and Bag Filter



Suction and Discharge Air Hose

Description

Industrial vacuum cleaner which is designed to suck coolant, swarf and oil from machine tool sumps, filter the swarf and pump filtered coolant back to machine sump for re-use.

Specs

- ✓ Strong suction thanks to 2x 1kW vacuum motors
- ✓ 330lt tank capacity (3mm sheet metal body)
- ✓ Sequential suction and discharge
- ✓ 63-200-400 μ re-usable bag filter
- ✓ When tank is full, vacuum motor air suction is closed by ball cock
- ✓ 330lt suction time with 2 motors < 2min, discharge time < 3min
- ✓ Various suction tools
- ✓ High manoeuvrability with swivel casters

Voltage (VAC)	Max Power (w)	Tank Capacity (lt)	Suction Rate (lt / min)	Discharge Rate (lt / min)	Length (mm)	Height (mm)	Width (mm)	Weight (kg)
220	2000	330	165	110	1450	1460-1240	660	162



Easy to Carry



Suction and Discharge Air Hose

Description

Industrial vacuum cleaner which is designed to suck coolant, swarf and oil from machine tool sumps, filter the swarf and pump filtered coolant back to machine sump for re-use.

Specs

- ✓ Strong suction thanks to 2x 1kW vacuum motors
- ✓ 200lt tank capacity (3mm sheet metal body)
- ✓ Sequential suction and discharge
- ✓ 63-200-400µ re-usable bag filter
- ✓ When tank is full, vacuum motor air suction is closed by ball cock
- ✓ 330lt suction time with 2 motors < 1.5min, discharge time < 2min
- ✓ Various suction tools
- ✓ High manoeuvrability with swivel casters

Voltage (VAC)	Max Power (w)	Tank Capacity (lt)	Suction Rate (lt / min)	Discharge Rate (lt / min)	Length (mm)	Height (mm)	Width (mm)	Weight (kg)
220	2000	200	135	100	950	1230-1020	660	107